



MoistureGard™ 2.0 Technical Data Sheet

PRODUCT DESCRIPTION

MoistureGard 2.0 is an opaque, black, multilayer co-extruded polypropylene film.

Width: 62 inches

Roll Length: 200 linear yards; 344 square yds/roll

Roll Weight: 61 pounds

TECHNICAL SPECIFICATIONS*

MoistureGard 2.0 properties

	Moisture Vapor Transmissions (grams/hour-square meter)	Permeance (grams/hour-square foot-in Hg)
Concrete	1.175	4.05
InterfaceFLOR MVB	0.018	0.061

PHYSICAL MECHANICAL PROPERTIES*

Clean up of tools and equipment may be accomplished using soap and water if the adhesive is in the wet state. Dried or tacky adhesive will require safety solvent.

PROPERTY	TEST	UNITS	SPECIFICATION
Thickness	Std	micron	4.0-4.5
Weight	Std	g/cm ²	0.9-1.0
Tensile CD	ASTM D882-95A	psi	2000-5000
Tensile MD	ASTM D882-95A	psi	3000-6000
1% Secant CD	ASTM D882-95A	psi	140,000-145,000
1% Secant MD	ASTM D882-95A	psi	145,000-155,000
Elongation CD	ASTM D882-95A	%	600-1100
Elongation MD	ASTM D882-95A	%	700-1200

*(as provided by product manufacturer)

PERFORMANCE RATING

Intended for use as a moisture barrier for installation of InterfaceFLOR modular carpet on concrete slabs with moisture levels up to 15 lbs. and pH up to 12 when tested in accordance with ASTM F1869-04.